US007554342B2

(12) **United States Patent**
Messenger et al.

(10) **Patent No.: US 7,554,342 B2**
(45) **Date of Patent: Jun. 30, 2009**

(54) **BISTABLE MICROMECHANICAL DEVICES**

(75) Inventors: **Robert K. Messenger**, Springville, UT (US); **Timothy W. McLain**, Provo, UT (US); **Jeffrey K. Anderson**, Provo, UT (US); **Larry L. Howell**, Orem, UT (US)

(73) Assignee: **Brigham Young University**, Provo, UT (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 25 days.

(21) Appl. No.: **11/875,024**

(22) Filed: **Oct. 19, 2007**

(65) **Prior Publication Data**

US 2008/0036478 A1 Feb. 14, 2008

Related U.S. Application Data

(63) Continuation of application No. 11/271,541, filed on Nov. 11, 2005.

(60) Provisional application No. 60/735,408, filed on Nov. 9, 2005, provisional application No. 60/627,736, filed on Nov. 11, 2004.

(51) **Int. Cl.**
G01R 27/08 (2006.01)

(52) **U.S. Cl.** **324/695**; 324/415

(58) **Field of Classification Search** 324/415, 324/695

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,355,712	A *	10/1994	Petersen et al.	73/1.38
5,445,006	A *	8/1995	Allen et al.	73/1.38
6,199,874	B1 *	3/2001	Galvin et al.	280/5.514
6,327,909	B1 *	12/2001	Hung et al.	73/514.16
6,969,996	B2 *	11/2005	Staple et al.	324/415

* cited by examiner

Primary Examiner—Timothy J. Dole
Assistant Examiner—Thomas F. Valone
(74) *Attorney, Agent, or Firm*—Steve McDaniel; Utah Valley Patent

(57) **ABSTRACT**

A micromechanical device may include one or more piezoresistive elements whose electrical resistance changes in response to externally or internally induced strain. The present invention leverages the piezoresistive properties of such devices to sense the positional state of the device. A sensing circuit may be integrated into the device that senses an electrical resistance of at least a portion of the micromechanical device and provides information regarding the positional state of the micromechanical device. The micromechanical device may be a compliant device that includes relatively flexible members such as mechanical beams or ribbons. The positional states may be continuous positional states (such as the position of an actuator) or discreet positional states (such as the positional state of a bistable memory device). In certain embodiments, the micromechanical device is a threshold detector that latches to a particular stable configuration when an applied force exceeds a selected value.

6 Claims, 5 Drawing Sheets